

SL HOPPER

Technical data / Dati tecnici

	SL 30 AF	SL 30 AV	SL 45 AF	SL 45 AV	
V - Hz	400 - 50 3~	400 - 50 3~	400 - 50 3~	400 - 50 3~	Voltage / Alimentazione¹
kW	30	30	45	45	Power / Potenza
IP	55	55	55	55	Electrical protection / Prot elettrica
mmH2O	5000	8500	5000	8500	Max waterlift / Depressione max
m ³ /h	1800	1300	2500	1900	Max air flow / Portata d'aria max
mm	140	140	140	140	Suction inlet / Ø bocchettone
Connection / Collegamento			Flange / Flangia		
lt.	1000	1000	1000	1000	Capacity / Capacità
cm	168x160x356h	168x160x356h	168x160x356h	168x160x356h	Dimensions / Dimensioni
kg	2080	2100	2310	2260	Weight / Peso
Discharge system / Sistema scarico			Manual discharge butterfly valve / Valvola a farfalla manuale ø250		
Control system / Sistema di controllo			Remote control / Controllo locale-remoto		
Primary filter / Filtro primario			30 sleeves / 30 tasche		
cm ² -mm		<i>Surface, diameter / Superficie, diametro</i>		160.000 - 120	
<i>Media, class / Media, classe (IEC 60335-2-69)²</i>			<i>Polyester / Poliestere - M</i>		
m ³ /m ² /h	112	81	156	118	<i>Air load on filter / Carico specifico sul filtro</i>
Cleaning system / Sistema di pulizia			Alternate chamber / Camera alternata		
Cartridge / Cartuccia			Safety filter / Filtro di sicurezza		
cm ²		70.000 - 270		<i>Surface, diameter / Superficie, diametro</i>	
Polyester / Poliestere - M			Air load on filter / Carico specifico sul filtro		



Sales Service and Rental